

MATERIAL SAFETY DATA SHEET
 OSHA Hazard Communication
 Standard (29 CFR 1910.1200)

SIMILAR TO OSHA FORM 20 AND 114
 US Department of Labor
 Printed on 7/02/91 at 09:42:07

Material Identity
 Jacquard Dye-na-Flow Colors

Seq. No. 1 Rev. No. 1
 ASTM D4236-89 Yes
 Certification

Rcvd Aug 2001

SECTION I MANUFACTURER'S NAME AND LOCATION 721-301/401508

Manufact. Name **Rupert, Gibbon & Spider**
 Address line 1 **F.O. Box 425**
 Address line 2 **Healdsburg, CA 95448**
 Address line 3 **USA**
 Info. Tel. No. **707-433-9577** Emerg. Tel. No. **1(800)468-6942**
 Prep. Date **6/26/91** Responsible Person **Michael Katz**
 Title **President**

SECTION II HAZARDOUS INGREDIENTS/IDENTITY/STANDARDS/CONTENT INFORMATION

Ingredient Listing	CAS No.	OSHA PEL	ACGIH TLV	STEL
Acrylic Polymer Emulsi	N/L	N/L	N/L	N/L
Defoamer	N/L	N/L	N/L	N/L
Surfactant	N/L	N/L	N/L	N/L
Silicone Emulsion	N/L	N/L	N/L	N/L
Acrylic Copolymer in A	N/L	N/L	N/L	N/L
Acrylic Copolymer in M	N/L	N/L	N/L	N/L
Caster Oil	N/L	N/L	N/L	N/L
Titanium Dioxide	13463-67-7	10 mg/m3	10 mg/m3	N/L
Pigments	Mixture	N/L	N/L	N/L

This product has not been tested in animals but the Toxicologist reviewing this product has judged the formulation to be "Not Rated Acutely Toxic". It is not likely to be an irritant to the eyes or skin. However, as with all chemical mixtures, it is prudent to avoid contact with eyes and skin..

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point **N/D** Deg. F (Cel) **N/D** Spec. Grav. **N/D**
 Melting Point **N/D** Deg. F (Cel) **N/D** (H2O=1)
 Vapor Pressure **N/D** Vapor Density **N/D**
 Evaporation Rate **N/D** Water Solubility **N/D**
 Odor **Odor of Latex paint.** Appearance **Colored liquid paint in 33 colors.**

SECTION IV FIRE and EXPLOSION HAZARD DATA

Flash Point **N/D** Deg. F.(Cel) **N/D** Flash Pt. Method **N/D**
 Lower Flam. Limit **N/D** Upper Flam. Limit **N/D**
 Exting. Medium **Use water, foam, carbon dioxide or dry chemical. This product not likely to burn when wet.**
 Specialized Fire Fighting Proc. **None required for this material. However, when fighting any fire, wear positive prassure self-contained NIOSH approved breathing equipment.**
 Unusual Fire & Explosion Hazard **sealed Containers may rupture; Paint films may burn. This product presents no unusual fire or explosion hazards.**

SECTION V REACTIVITY DATA

Stable (Unstable) **Yes** Conditions **Strong oxidizing agents. to avoid**
 Incompat. (Avoid) **Avoid strong oxidizing agents.**
 Haz. Decomp. (y/n) **Not Likely** Haz. Polym. (yes/no) **Not Likely.**
 Cond. to Avoid. **None known.**

Confirm all information prior to use

Abbreviations: **Not Applicable N/A.. Not Flammable N/F**
Not Known N/K

Ceiling Value C
Not Determined N/D
Not Listed N/L
TLV

Permissible Exposure Limit **PEL** ACGIH Threshold Limit Value **TLV**
 The data shown is taken from sources judged to be reliable. The user should judge both the accuracy and the suitability of this information for any attention or purpose. No other warranty is given. (TLV Reg. TM, ACGIH)

MATERIAL SAFETY DATA SHEET
 OSHA Hazard Communication
 Standard (29 CFR 1910.1200)

SIMILAR TO OSHA FORMS 20 AND 174
 US Department of Labor
 Printed on 7/02/91 at 09:42:10

Material Identity **Jacquard Textile Color**

SECTION VI HEALTH HAZARD DATA

Routes of Entry: Inhalation Vapors can be inhaled; not likely in toxic amts..
 Skin Not likely in toxic amounts. Ingest. Very young children may drink
 paint. Keep paint out of reach.

Health Hazards None known for the usual and ordinary uses of this product.
 NTP Carcinogen N/L IARC Carcinogen N/L OSHA Carcinogen N/L
 Signs/Symptoms Symptoms of irritation are not likely to occur when using this
 of Exposure and similar water based latex paint mixtures.
 Medical Conditions N/K
 to Avoid

First Aid Eye contact: Carefully flush for 15 minutes. If irritation
 persists, contact physician. Skin: Wash with soap and water.
 Inhalation: Remove to fresh air.

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE

Spill Contain spill. Spill area will be slippery. Recover as
 much as possible for reuse. Spread commercial absorbant
 over remainder and place into sealed container for
 disposal.

Waste Disp Dispose of all waste material in accordance with all
 applicable Federal, State and Local regulations. Most
 states prohibit disposal of liquids in landfills.

Precautions None are likely to be needed.
 Other Precautions As with all chemicals good industrial hygiene and proper
 work habits should be observed.

SECTION VIII CONTROL MEASURES

Resp. Protect. Not usually required.
 Local Exhaust May be used to prevent routine inhalation.
 Spec. Local. Exh. N/A
 Mech. Exhaust Mechanically exhaust vapors at point(s) of application.
 Other Mech. Exhaust N/A

Protect. Gloves Not normally needed.

Eye Protect Splash goggles

Protect. Clothing N/A

Work Practices As with all chemicals, good industrial hygiene and proper
 work habits should be observed. Clean up work area after
 use.

Confirm all information prior to use

Abbreviations: Not Applicable N/A.. Not Flammable N/F

Not Known N/K

Permissible Exposure Limit PEL

ACGIH Threshold Limit Value TLV

e data shown is taken from sources judged to be reliable. The user should

Ceiling Value C

Not Determined N/D

Not Listed N/L