SAFETY DATA SHEET

I T E M 4 0 5 2 9 8

1. Identification

Product identifier HP Color LaserJet CE323A Magenta Print Cartridge

Other means of identification Not available.

Recommended use This product is a magenta toner preparation that is used in HP LaserJet Pro CM1415, CP1525 series

printers.

Recommended restrictions

Company identification

None known. HP

1501 Page Mill Road Palo Alto, CA 94304-1112

United States

Telephone 650-857-5020

HP health effects line

(Toll-free within the US) 1-800-457-4209

(Direct) 1-760-710-0048 **HP Customer Care Line**

(Toll-free within the US) 1-800-474-6836

(Direct) 1-208-323-2551

Email: hpcustomer.inquiries@hp.com

2. Hazard(s) identification

Physical hazards Not classified. Not classified. **Health hazards Environmental hazards** Not classified. **OSHA** defined hazards Not classified.

Label elements

None. **Hazard symbol** Signal word None.

Not available. **Hazard statement**

Precautionary statement

Not available. **Prevention** Response Not available. Not available. Storage **Disposal** Not available.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information This product is not classified as hazardous according to OSHA CFR 1910.1200 (HazCom 2012).

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Styrene acrylate copolymer		Trade Secret	<85
Pigment	Pigment	Trade Secret	<10
Wax	Wax	Trade Secret	<10
Amorphous silica	Amorphous silica	7631-86-9	<3
Titanium dioxide		13463-67-7	<1

4. First-aid measures

Move person to fresh air immediately. If irritation persists, consult a physician. Inhalation

Material name: CE323A 1/6

12324 Version #: 04 Revision date: 12-Oct-2015 Issue date: 16-Apr-2015 Skin contact Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation

develops or persists.

Do not rub eyes. Immediately flush with large amounts of clean, warm water (low pressure) for at Eye contact

least 15 minutes or until particles are removed. If irritation persists, consult a physician.

Ingestion Rinse mouth out with water. Drink one to two glasses of water. If symptoms occur, consult a

physician.

Most important

symptoms/effects, acute and

Not available.

delayed

5. Fire-fighting measures

Suitable extinguishing media

CO2, water, or dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards arising from

the chemical

Not applicable.

Special protective equipment

and precautions for

Not available.

firefighters

Fire-fighting

equipment/instructions

Specific methods None established.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Minimize dust generation and accumulation.

If fire occurs in the printer, treat as an electrical fire.

Methods and materials for containment and cleaning up

Not available.

Environmental precautions

Do not flush into surface water or sanitary sewer system. See also section 13 Disposal

considerations.

7. Handling and storage

Precautions for safe handling

Keep out of the reach of children. Avoid inhalation of dust and contact with skin and eyes. Use with adequate ventilation. Keep away from excessive heat, sparks, and open flames.

Value

6 mg/m3

Form

Conditions for safe storage,

including any incompatibilities

Components

Keep out of the reach of children. Keep tightly closed and dry. Store at room temperature. Store

away from strong oxidizers.

Type

TWA

8. Exposure controls/personal protection

Occupational exposure limits

Amorphous silica (CAS

7631-86-9)

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

13463-67-7) US. ACGIH Threshold Limit Values Components Type Value Titanium dioxide (CAS 10 mg/m3 13463-67-7)	US. NIOSH: Pocket Guide to C Components	Chemical Hazards Type	Value	
13463-67-7) US. ACGIH Threshold Limit Values	13463-67-7)		10 mg/m3	
· · · · · · · · · · · · · · · · · · ·			Value	
	Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.

Biological limit values No biological exposure limits noted for the ingredient(s).

Material name: CE323A SDS US Exposure guidelines USA OSHA (TWA/PEL): 15 mg/m3 (Total Dust), 5 mg/m3 (Respirable Fraction)

ACGIH (TWA/TLV): 10 mg/m3 (Inhalable Particulate), 3 mg/m3 (Respirable Particulate)

Amorphous silica: USA OSHA (TWA/PEL): 20 mppcf 80 (mg/m3)/%SiO2, ACGIH (TWA/TLV): 10

mg/m3

TRGS 900 (Luftgrenzwert) - 10 mg/m3 (Einatembare partikel), 3 mg/m3 (Alveolengängige fraktion)

UK WEL: 10 mg/m3 (Respirable Dust), 5 mg/m3 (Inhalable Dust)

Appropriate engineering

controls

Use in a well ventilated area.

Individual protection measures, such as personal protective equipment

Eye/face protection Not available.

Skin protection

Hand protectionNot available.OtherNot available.Respiratory protectionNot available.Thermal hazardsNot available.

9. Physical and chemical properties

Appearance Fine powder
Physical state Solid.
Color Magenta

Odor Slight plastic odor
Odor threshold Not available.

PH Not applicable

Melting point/freezing point Not available.

Initial boiling point and Not applicable

boiling range

Flash point Not applicable
Evaporation rate Not applicable
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower Not fla

(%)

Not flammable

Flammability limit -

upper (%)

Not available.

Explosive limit - lower

(%)

Explosive limit - upper

(%)

Not available.

Not available.

Vapor pressure Not applicable

Solubility(ies)

Solubility (water) Negligible in water. Partially soluble in toluene and xylene.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature Not applicable

Decomposition temperature Not available.

Viscosity Not applicable

Other information

Percent volatile 0 % estimated

Softening point 176 - 266 °F (80 - 130 °C)

Specific gravity 1 - 1.2

Material name: CE323A SDS US

10. Stability and reactivity

Reactivity Not available.

Chemical stability Stable under normal storage conditions.

Possibility of hazardous

reactions

Will not occur.

Conditions to avoid Imaging Drum: Exposure to light

Incompatible materials Strong oxidizers

Hazardous decomposition

products

Carbon monoxide and carbon dioxide.

11. Toxicological information

Symptoms related to the physical, chemical and toxicological characteristics

Not available.

Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye

Based on available data, the classification criteria are not met.

irritation

Respiratory or skin sensitization

Respiratory sensitizationBased on available data, the classification criteria are not met. **Skin sensitization**Based on available data, the classification criteria are not met.

Germ cell mutagenicityNegative, does not indicate mutagenic potential (Ames Test: Salmonella typhimurium)

Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

IARC Monographs. Overall Evaluation of Carcinogenicity

Amorphous silica (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans.

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

Reproductive toxicityBased on available data, the classification criteria are not met. **Specific target organ toxicity**Based on available data, the classification criteria are not met.

- single exposure

Specific target organ toxicity

- repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Further information Complete toxicity data are not available for this specific formulation

Refer to Section 2 for potential health effects and Section 4 for first aid measures.

Components Species Test Results

Amorphous silica (CAS 7631-86-9)

Acute *Oral*

LD50 Mouse > 15000 mg/kg

Rat > 22500 mg/kg

12. Ecological information

Ecotoxicity

Product		Species	Test Results	
CE323A				
Aquatic				
Fish	LL50	Fish	> 1000 mg/l, 96 Hours	

Material name: CE323A SDS US

12324 Version #: 04 Revision date: 12-Oct-2015 Issue date: 16-Apr-2015

Components Species Test Results

Titanium dioxide (CAS 13463-67-7)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) > 1000 mg/l, 48 hours
Fish LC50 Mummichog (Fundulus heteroclitus) > 1000 mg/l, 96 hours

Persistence and degradabilityNot available.Bioaccumulative potentialNot available.Mobility in soilNot available.Other adverse effectsNot available.

13. Disposal considerations

Disposal instructionsDo not shred toner cartridge, unless dust-explosion prevention measures are taken. Finely

dispersed particles may form explosive mixtures in air. Dispose of in compliance with federal, state,

and local regulations.

HP's Planet Partners (trademark) supplies recycling program enables simple, convenient recycling of HP original inkjet and LaserJet supplies. For more information and to determine if this service is available in your location, please visit http://www.hp.com/recycle.

14. Transport information

Further information Not a dangerous good under DOT, IATA, ADR, IMDG, or RID.

15. Regulatory information

US EPA TSCA Inventory: All chemical substances in this product comply with all rules or orders

under TSCA.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 No

Hazardous chemical

Other federal regulations

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Amorphous silica (CAS 7631-86-9) Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Titanium dioxide (CAS 13463-67-7)

Material name: CE323A SDS US

US. Pennsylvania Worker and Community Right-to-Know Law

Amorphous silica (CAS 7631-86-9) Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

TITANIUM DIOXIDE (AIRBORNE, UNBOUND Listed: September 2, 2011

PARTICLES OF RESPIRABLE SIZE) (CAS 13463-67-7)

Regulatory information

All chemical substances in this HP product have been notified or are exempt from notification under chemical substances notification laws in the following countries: US (TSCA), EU (EINECS/ELINCS), Switzerland, Canada (DSL/NDSL), Australia, Japan, Philippines, South Korea, New Zealand, and China

16. Other information, including date of preparation or last revision

Issue date16-Apr-2015Revision date12-Oct-2015

Version # 04

Disclaimer This Safety Data Sheet document is provided without charge to customers of HP. Data is the most

current known to HP at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other

countries.

Manufacturer information HP

11311 Chinden Boulevard Boise, ID 83714 USA (Direct) 1-503-494-7199

(Toll-free within the US) 1-800-457-4209

Explanation of abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

CFR Code of Federal Regulations

COC Cleveland Open Cup

DOT Department of Transportation

EPCRA Emergency Planning and Community Right-to-Know Act (aka SARA)

IARC International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RCRA Resource Conservation and Recovery Act

REC Recommended

REL Recommended Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986

STEL Short-Term Exposure Limit

TCLP Toxicity Characteristics Leaching Procedure

TLV Threshold Limit Value

TSCA Toxic Substances Control Act
VOC Volatile Organic Compounds

Material name: CE323A SDS US