Safety Data Sheet (SDS) for Kerosene Thermometers

Per OSHA HCS 2012 (29 CFR 1910.1200)

Industrial and educational thermometers are considered "manufactured articles," and as such, do not require a SDS. Per 29CFR 1910.1200(c), "Definitions. Article means a manufactured item other than a fluid or particle: (i) which is formed to a specific shape or design during manufacture; (ii) which has end use function(s) dependent in whole or in part upon its shape or design during use; and (iii) which under normal conditions of use does not release more than very small quantities, e.g., minute or trace amounts of a hazardous chemical (as determined under paragraph (d) of this section), and does not pose a physical hazard or health risk..." This SDS is provided for information only.

If broken, the thermometer may release a small quantity of liquid, which should be dealt with using the information provided in this SDS (see Section 6 "Accidental Release Measures").

SECTION 1-IDENTIFICATION

Product name: Kerosene Thermometer

Other names:- Student Thermometer

Proper shipping name: Dangerous Goods in Apparatus

Recommended use of the article and restrictions on use:

Thermometer (temperature measurement)

Temperature range for use of the thermometer is marked on the article. Do not subject the thermometer to temperatures outside the marked range.

Manufacturer/Supplier Name: United Scientific Supplies, Inc.

3055 N. Oak Grove Ave., Waukegan, IL 60087 USA

Emergency phone No.: 1-800-222-1222 (American Association of Poison Control Centers)

SECTION 2-HAZARDS IDENTIFICATION

GHS Classification (kerosene filling, CAS 8008-20-6): Flammable Liquid Category 3 H226 H315

Skin Irritant Category 2

For text of H-phrases see section 16

GHS Label elements(kerosene filling, CAS 8008-20-6):

Hazard symbols





Signal word

Warning

Hazard statements

H226 - Flammable liquid and H315 - Causes skin irritation

Precautionary statements

P210 - Keep away from heat, sparks, open flames, and hot surfaces. No smoking.

P233 - Keep containers tightly closed

P240 - Ground/bond container and receiving equipment

P241 – Use explosion-proof electrical/ventilation/lighting/... equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge

Other hazards: - No additional information available

SECTION 3-COMPOSITION/INFORMATION ON INGREDIENTS

The thermometer body material is glass, judged non-hazardous. The thermometric liquid is kerosene blended with <0.1% red dye for visibility. The quantity of red dye is below the reporting level.

CAS No.	Chemical Name	wt% by weight	Classification (GHS-US)
8008-20-6	Kerosene	100.0	Flammable liquid 3, H226 Skin irritant 2, H315 Aspiration toxicity 1, H304 Aquatic chronic hazard 2, H411
Synonyms	Kerosine, Lamp oil, Paraffin (UK)		



SECTION 4-FIRST AID MEASURES

Description of necessary first aid measures

General

- 1. Never give anything by mouth to an unconscious person.
- 2. If the patient feels unwell, seek medical attention and show this SDS if possible.

Eye:

Rinse immediately with copious warm water. Obtain medical attention if pain, blinking, or redness persist

Skin:

- 1. Remove contaminated clothing, shoes, and leathery articles, use cleaning procedure before reuse or waste treatment.
- 2. Wash affected area thoroughly with soap and water.
- 3. Call a Physician if irritation develops or persists.

Ingestion:

- 1. Rinse mouth. Do NOT induce vomiting.
- Seek medical attention.

Inhalation:

- 1. Remove from further exposure and allow to breathe freshair.
- 2. Lay patient down. Keep warm and rested.

Most important symptoms/effects, acute and delayed

After skin contact: Causes skin irritation

Indication of immediate medical attention and special treatment needed, if necessary

Treat symptomatically

SECTION 5-FIRE FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Foam, dry powder, carbon dioxide, water spray, sand.

Unsuitable extinguishing media: Do not use a heavy water stream

Special hazards arising from the substance

- 1. Liquid and vapor are flammable.
- 2. May form a flammable or explosive vapor/air mixture.
- 3. Reactivity: This substance is stable under normal handling and storage conditions.

SECTION 6-ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedure

1. Personal protective equipment (See also specifications in Section 8)

Eyes: Chemical safety goggles are recommended.

Skin: Wear appropriate protective gloves to avoid skin contact.

Clothing: When direct contact is likely, use rubberized clothing, apron and boots.

Respiratory: When limits are exceeded, wear a respirator approved by NIOSH/MSHA for protection against organic dust,

mists and vapors.

- 2. Remove all sources of ignition. No smoking, naked lights or ignition sources. Ventilate area of leak or spill.
- 3. Keep unnecessary and unprotected personnel from entering. Evacuate personnel from the danger area. Consult with an expert about the emergency procedures.

Environmental precautions

- 1. Prevent spillage from entering drains, surface, and groundwater.
- 2. Contain and recover liquid when possible. Use non-sparking tools and equipment.
- 3. Collect liquid in an appropriate container or absorb with an inert material (e.g. vermiculite, dry sand, earth), and place in a chemical waste container.
- Report large accidental spills/releases (multiple thermometer contents) to local/State government.

Special protective equipment and precautions for fire-fighters

- 1. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering the environment.
- 2. Use caution when fighting any chemical fire.
- 3. Do not enter the fire area without proper protective equipment, including respiratory protection

Methods and materials for containment and cleaning up

- 1. Remove all ignition sources.
- 2. Clean up all spills immediately.
- 3. Avoid breathing vapors and contact with skin and eyes.
- 4. Control personal contact by using protective equipment.
- 5. Contain and absorb small quantities with vermiculite or other absorbent material.
- 6. Wipe up
- 7. Collect residues in a container for flammable waste

SECTION 7-HANDLING AND STORAGE

Precautions for safe handling of liquid from broken thermometers

- 1. Avoid sources of ignition or sparking.
- 2. Clean up spilled liquid immediately as described in the previous section
- 3. Avoid contact with broken glass pieces. Store glass pieces in absorbent material for safe disposal
- Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities

- 1. Store thermometers in original containers. Protect from mechanical shocks glass is fragile.
- 2. No smoking, naked lights, heat or ignition sources near broken thermometers.
- Store away from incompatible materials in a cool, dry well ventilated area. Incompatible materials (released liquid): strong bases, strong acids Incompatible conditions: direct sunlight, heat sources

SECTION 8-EXPOSURE CONTROLS, PERSONAL PROTECTION

Control Parameters:

Kerosene thermometer: ACGIH: not applicable; OSHA: not applicable

Kerosene (8008-20-6): ACGIH TWA (mg/m³): 200; OSHA: not applicable

Engineering Controls: Provide adequate general and local exhaust ventilation

Personal Protective Equipment: Protective clothing, Protective goggles

Hand protection: Not required under normal conditions of use
Eye protection: Where eye contact may occur, wear eye protection
Skin/body protection: Not required under normal conditions of use
Respiratory protection: Where exposure through inhalation may occur,
respiratory protection equipment is recommended

Other information: Do not eat, drink, or smoke during use.

SECTION 9-PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Transparent red liquid	Upper/lower explosive limits : 0.7%/5%		
Odor : no data available	Vapor Pressure : 1 mmHg @ 20°C		
Odor threshold : no data available	Vapor Density : 4.5 (air=1)		
pH : No data available	Relative density (water=1): approximately 0.84		
Melting/Freezing Point: No data available	Solubility in water : insoluble in water (mixture)		
Initial boiling point/boiling range: 175 - 325°C	Solubility in water: ≤0.0007g/100ml (components)		
Flash point : 38°C	Auto-ignition temperature : 210°C		
Evaporation Rate (butyl acetate=1): No data available	Decomposition temperature : No data available		
Flammability (solid/gas) : No data available	Viscosity : No data available		
Molecular Formula : Mixture of alkanes C _n H _(2n+2)	Molecular Weight : Not applicable		

SECTION 10-STABILITY AND REACTIVITY

Reactivity

Thermometric liquid is stable under normal handling and storage conditions

Chemical stability

Liquid and vapor are flammable. May form flammable/explosive vapor/air mixture

Possibility of hazardous reaction

Has not been reported.

Condition to avoid

Direct sunlight, extremely high or low temperatures, open flame, overheating, heat, sparks

Incompatible materials

Strong acids, strong bases

Hazardous decomposition products

Fumes, carbon monoxide, carbon dioxide, flammable hydrocarbons

SECTION 11-TOXICOLOGICAL INFORMATION

Toxicological effects:

Acute toxicity: Not classified (Based on available data, the classification criteria are not met)

Kerosene (8008-20-6)

LD50 oral rat: >5000mg/kg (rat) LD50 dermal rat: >2000mg/kg (rat) LD50 dermal rabbit: >2000mg/kg (rabbit) LC50 inhalation rat: >5.28mg/l/4h (rat)

Skin corrosion/irritation: Causes skin irritation

Serious eye damage/irritation: Not classified (Based on available data, the classification criteria are not met)

Germ cell mutagenicity: Not classified (Based on available data, the classification criteria are not met)

Carcinogenicity: Not classified (Based on available data, the classification criteria are not met)

IARC group: 3 - Not classifiable

Reproductive toxicity: Not classified (Based on available data, the classification criteria are not met)

Specific organ toxicity (single exposure): Not classified (Based on available data, the classification criteria are not met)

Specific organ toxicity (repeated exposure): Not classified (Based on available data, the classification criteria are not met)

Aspiration hazard: Not classified (Based on available data, the classification criteria are not met)

Potential adverse human health effects

and symptoms: Not classified (Based on available data, the classification criteria are not met)

Symptoms/injuries after skin contact: Causes skin irritation

SECTION 12-ECOLOGICAL INFORMATION

Ecotoxicity

Ecology: water: Toxic to aquatic life with long lasting effects

Kerosene (8008-20-6)

LC50 Fish 1: 18-25 mg/l (96 h; Pisces)
LC50 Other aquatic organisms 1: 1-100 mg/l
EC50 Daphnia 1: 1.4-21 mg/l (Daphnia magna)
LC50 Fish 2: 45 mg/l (Pimephales promelas)
TLM Fish 1: 2990 ppm (24 h: Lepomis macrochirus)
Threshold limit other aquatic organisms 1: 1-100

Threshold limit algae 1: 4-8 (algae)

Persistence and degradability

Kerosene Thermometer: May cause long term adverse effects in the environment

Kerosene (8008-20-6): Biodegradable in water. Readily biodegradable in water under anaerobic conditions. Forms sediment

in water. Biodegradable in soil. Biodegradable in soil under anaerobic conditions. Adsorbs into soil.

Bioaccumulative potential: Kerosene Thermometer: Not established.

Kerosene (8008-20-6): Log Pow: 3.3-6 (calculated); Bioaccumulative.

Mobility in soil: Kerosene (8008-20-6): Surface tension: 0.02-0.03 N/m

Other adverse effects: Kerosene Thermometer:

Effect on the ozone layer: Not applicable

Effect on the global warming: No known ecological damage caused by this product Other information:

Avoid release of thermometric liquid to the environment



Classification according to Directive 67/548/EEC (DSD) or 1999/45/EC (DPD) (kerosene):

Xi: R38 N: R51/53

SECTION 13-DISPOSAL CONSIDERATIONS

Waste disposal recommendations: Dispose in a safe manner in accordance with local/state/national regulations

Additional information:

Handle broken glass thermometers with care – glass may be contaminated with liquid.

Ecology – waste materials: Avoid releases to the environment.

SECTION 14-TRANSPORTATION INFORMATION

	Shipping Name	Dangerous Goods in Apparatus		A
US DOT	Hazard Class	9	Hazard Labels	
	UN Number	3363		
	Packing Group	n/a		9//
	Shipping Name	Dangerous Goods in Apparatus		
	Hazard Class	9		A
	UN Number	3663		
Sea(IMO/IMDG)	Packing Group	n/a	Hazard Labels	
	MARPOL	Not a DOT "Marine Pollutant" per 49 CFR 171.8.		
	Shipping Name	Dangerous Goods in Apparatus		
Air(ICAO/IATA)	Hazard Class	9	Hazard Labels	
	Subsidiary Class	n/a		
	Packing Group	n/a		
RID/ ADR	No information available.			
Canadian TDG	Shipping Name	Dangerous Goods in Apparatus		A
	Hazard Class	9	Hazard Labels	
	UN Number	3363	nazaru Lapeis	
	Packing Group	n/a		9
	Subsidiary Class	n/a		



SECTION 15-REGULATORY INFORMATION

US Federal Regulations:

Kerosene Thermometer: None known

Kerosene (8008-20-6): Listed on the United States TSCA (Toxic Substances Control Act) inventory.

International Regulations:

Canada: No additional information available

EU Regulations: No additional information available

Classification according to EC Regulation No.1272/2008 (CLP) (kerosene):

Flammable Liquid 3 H226 Skin irritant 2 H315 Aquatic chronic 2 H411

SECTION 16-OTHER INFORMATION

Full Text of H-phrases:

Aquatic Chronic 2 Hazardous to the aquatic environment – chronic hazard category 2

Asp. Tox.1 Aspiration hazard category 1
Flammable liquid 3 Flammable liquids category 3
Skin irritant 2 Skin corrosion/irritation category 2
H226 Flammable liquid and vapor

H304 May be fatal if swallowed and enters airways

H315 Causes skin irritation

H411 Toxic to aquatic life with long lasting effects

NFPA Hazard Classification (kerosene):

Health: 1- Exposure could cause irritation but only minor


residual injury even if no treatment is given.

Fire: 3- Liquids and solids that can be ignited under

almost all ambient conditions.

Reactivity: 0- Normally stable, even under fire exposure

conditions, and not reactive with water.



References and sources

- 1. Chemwatch Data Bank, 2005-1
- 2. SDS, GHS HazCom 2012
- 3. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16 December 2008

Version	Date	Remark		
Version 3	11/032022	Update.		
Prepared by	United Scientific Supplies, Inc			

Disclaimer of Expressed and implied Warranties:

United Scientific Supplies, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. UNITED SCIENTIFIC SUPPLIES, INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, UNITEDSCIENTIFIC SUPPLIES, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

UNITED SCIENTIFIC SUPPLIES, INC. (ph) 847-336-7556 www.unitedsci.com