160-750/424936

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard Must Be Consulted for Specific Requirements

Red March 2002

Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

IDENTITY (As Used on Label and List)
Prang Tempera Paint
Ready To Use

NOTE: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that

SECTION I			
Manufacturer's Name		Emergency Telephone Number	
DIXON TICONDEROGA			(419) 625-9545
Address(Number, Street, City, State, and ZIP)	· · · · · · · · · · · · · · · · · · ·	Telephone Number for Information	1
			(419) 625-9545
1706 HAYES AVENUE		Date Prepared	
SANDUSKY, OHIO 44870			02/22/02
		Signature of Preparer (optional)	
SECTION II - HAZARDOUS INGREDIENTS/INDENTITY INFORMATION	ON		
Hazardous Components			Other Limits
(Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Recommended %Optional

Products bearing the CP Certified Products or AP Approved Products seals of the Art and Creative Materials Institute, Inc. are certified in a program of Toxicological evaluation by a Medical expert, subject to review by the Institute's Toxicological Advisory Board, to contain no materials in sufficient quantities to be toxic or injurious to humans or cause acute or chronic health problems.

CONFORMS TO ASTM-4236

SECTION III - PHYSICAL	CHEMICAL CHARACTE	RISTICS					***		
Boiling Point			Specific Gravity (H2O = 1)						
	N/A	A			Greater than 1.0				
Vapor Pressure (mm Hg)	N/A			Melting Point					
Vapor Density (Air=1)				Evaporation Rate					
	N/A			(Butyl Acetate = 1)	N	/A			
Solubility In Water	Nil								
Appearance and Odor	Colorec	l liquid, nearly odo	orless						
SECTION IV - FIRE AND									
Flash Point (Method Used)	N/			Flammable Limits	\$1/A	LEL N/A	UEL	A	
Extinguishing Media	The second secon	***			N/A	j N/A	N/.	<u>A</u>	
Special Fire Fighting Procedure Containers may be		y, Foam, CO2 and may release to	oxic or other irri	itating gases	,				
Unusual Fire and Explosion Haz A self contained breathin	erds g apparatus should be use	d for this evaneurs							
(Reproduce Locally)	g apparatos silvota de doc	a tor una exposure	,	OSHA 174, SE	PT. 1985		···.		
SECTION V - REACTIVITY	Y DATA		**************************************						
Stability	Unstable		Conditions	To Avoid					
	Stable	YES			NONE				
Incompatibility (Materials To Av	eid)		MONE						
Hazardous Decomposition or By			NONE						
As with all burning organic		nd other toxic fum	ac may ba aisa	n off					
Hazardous	May Occur	na oaioi toxic iaiii	Conditions 7			· ·	···		
Polymerization	may occar		Conditions	18 AVOIG					
	Will Not Occur	YES			NONE				
SECTION VI - HEALTH HA	ZARD DATA								
Route(s) Of Entry:		Inhalation?	NO	Skin? Ingestion?					
Health Hagges (Acute and Chro	aic)		NO	YES		YI	ES		

Conforms to ASTM D-4236 Carcinogenicity: NTP? IARC Monographs? OSHA Regulated? N/A N/A N/A Signs and Symptoms of Exposure N/A Medical Conditions Generally Aggravated by Exposure N/A Emergency and First Aid Procedures Eyes--flush with copious amounts of water and contact a physician Contact with skin-Wash area with soap and water; Ingestion-seek medical attention; SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE Steps to Be Taken in Case Material Is Released or Spilled Contain and place in approved containers. Waste Disposal Method Dispose of per all Local, State, and Federal Regulations. Precautions to Be Taken in Handling and Storing Do not store near heat or open flame. Other Precautions None **SECTION VIII - CONTROL MEASURES** Respiratory Protection (specify Type) N/A Ventilation Local Exhaust Special OKAY N/A Mechanical (General) Other OKAY N/A Protective Gloves Eye Protection N/A YES Other Protective Clothing or Equipment N/A Work/Hygenic Practices Contents will stain most fabrics, use of smocks, gloves, etc to protect personel clothing is suggested. Wash hands and surfaces after use.

Page 2

* USGPO 1986-491-529/45775