SDS No.: CC0333 SAFETY DATA SHEET

Section 1 Identification Page E1 of E2

INNOVATING SCIENCE®

"Cutting edge science for the classroom"

by Aldon Corporation 221 Rochester Street Avon, NY 14414-9409 (585) 226-6177 CHEMTREC 24 Hour Emergency Phone Number (800) 424-9300

For laboratory and industrial use only. Not for drug, food or household use.

Product CHROMATOGRAPHY SOLVENT (9:1)

Synonyms Acetone/Ethyl alcohol (9:1)

Section 2 Hazards identification

Signal word: DANGER Pictograms: GHS02 / GHS07

Target organs: Eyes, Central nervous system, Liver, Kidneys





GHS Classification:

Flammable liquid (Category 2) Eye irritation (Category 2A) STOT-SE (Category 3)

GHS Label information: Hazard statement:

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Supplemental information:

EUH066: Repeated exposure may cause skin dryness or cracking.

Precautionary statement:

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P261: Avoid breathing mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for 15 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+P313: If eye irritation persists: Get medical attention.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing

P312: Call a POISON CENTER or doctor if you feel unwell.

P370+P378: In case of fire: Use dry chemical, alcohol foam, carbon dioxide or water spray to extinguish.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405+P235: Store locked up. Keep cool.

P501: Dispose of contents/container to a licensed chemical disposal agency in accordance with local/regional/national regulations.

Hazards not otherwise classified:

Health hazards not otherwise classified (HHNOC) - Not Known Physical bazards not otherwise classified (PHNOC) - Not Known

Section 3 Composition / inf	ormation on ingredients			
Chemical Name	CAS#	%	EINECS	
Acetone	67-64-1	90%	200-662-2	
Ethyl alcohol, denatured*	64-17-5	10%	200-578-6	
* Denaturants:				
Isopropyl alcohol	67-63-0		200-661-7	
Methanol	67-56-1		200-659-6	
Methyl isobutyl ketone	108-10-1		203-550-1	

Section 4 First aid measures

INGESTION: HARMFUL IF SWALLOWED. Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: HARMFUL IF INHALED. CAUSES RESPIRATORY TRACT IRRITATION. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: CAUSES SEVERE EYE IRRITATION. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN ABSORPTION: REPEATED OR PROLONGED CONTACT MAY CAUSE DRYING AND DEFATTING OF SKIN. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

Section 5 Fire fighting measures

Suitable Extinguishing Media: Carbon dioxide, dry chemical, dry sand, alcohol foam.

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep fire-exposed containers cool.

Specific Hazards: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Acetone is extremely flammable and its vapors form explosive mixtures with air. Dangerous when exposed to heat, sparks, flame or oxidizing agents.

Section 6 Accidental release measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways.

Containment and Cleanup: Remove all sources of ignition. Absorb with inert dry material, sweep or vacuum up and place in a suitable container for proper disposal. Wash spill area with soap and water.

Page E2 of E2 Section 7 Handling and storage

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Avoid contact with eyes, skin and clothing. Do not inhale vapors, spray or mist. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, well-ventilated area away from incompatible substances. Keep away from ignition sources.

Section 8	Exposure controls / personal protection						
Exposure Limits:	Chemical Name	ACGIH (TLV)	OSHA (PEL)	NIOSH (REL)			
Exposure Limits.	Acetone	TWA: 500 ppm; STEL: 750 ppm	TWA: 1000 ppm / 2400 mg/m ³	TWA: 250 ppm / 590 mg/m ³			

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If misty conditions prevail, work in fume hood or wear a NIOSH/MSHAapproved respirator.

Section 9 Physical and chemical properties

Appearance: Clear, colorless liquid. Odor: Fragrant, mint-like odor. Odor threshold: Data not available

pH: Data not available

Melting / Freezing point: Approximately 95°C (139°F)*

Boiling point: 56°C (133°F)*

Flash point: -20°C (-4°F) CC*

Evaporation rate (Butyl acetate = 1): >6.0 Flammability (solid/gas): Data not available Explosion limits: Lower / Upper: 2.5% / 13%* Vapor pressure (mm Hg): 180*

Vapor density (Air = 1): 2.00* Relative density (Specific gravity): 0.8* Solubility(ies): Soluble in water.

Partition coefficient: (n-octanol / water): Log Pow: -.24*

Auto-ignition temperature: 465°C (869°F)* Decomposition temperature: Data not available Viscosity: Data not available.

Molecular formula: Mixture Molecular weight: Mixture

*Acetone

Section 10 Stability and reactivity

Chemical stability: Stable Hazardous polymerization: Will not occur. Conditions to avoid: Excessive temperatures, heat, sparks, open flame and other sources of ignition.

Incompatible materials: Chloroform, chromic anhydride, hydrogen peroxide, nitric compounds, acids, strong oxidizers, alkalies, inorganic acids, halogens.

Hazardous decomposition products: Oxides of carbon.

Section 11 **Toxicological information**

Acute toxicity: Oral-rat LD50: 5,800 mg/kg; Inhalation-rat LC50: 76 mg/L/4 hours [Acetone] / Oral-rat LD50: 7060 mg/kg; Inhalation-rat LC50: 124.7 mg/l/4hours [Ethanol]

Skin corrosion/irritation: Skin-rabbit - Slight irritant. [Acetone]

Serious eye damage/irritation: Eyes-rabbit - Severe irritant. [Acetone]

Respiratory or skin sensitization: Data not available

Germ cell mutagenicity: Data not available

Carcinogenity: Data not available

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

IARC classified: Group 3: Not classifiable as to its carcinogenicity to humans. [Isopropanol]

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

CA Prop 65: A WARNING! : This product can expose you to chemicals including Methanol and Methyl isobutyl ketone, which are known to the State of California to cause cancer and birth defects or other reproductive harm.

Reproductive toxicity: Data not available

STOT-single exposure: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects. [Acetone]

STOT-repeated exposure: Data not available Aspiration hazard: Data not available

Potential health effects:

Inhalation: Inhalation may cause cough, sore throat, confusion, headache, dizziness, drowsiness, unconsciousness.

Ingestion: Ingestion causes nausea, vomiting, and other symptoms same as inhalation.

Skin: Contact with skin causes irritation, dry and/or defatting on prolonged contact.

Eyes: Contact with eyes causes redness, pain and blurred vision.

Signs and symptoms of exposure: See Potential health effects above. Exercise appropriate procedures to minimize potential hazards.

Additional information: RTECS #: AL3150000 [Acetone] / KQ6300000 [Ethanol]

Section 12 **Ecological information**

Toxicity to fish: Gambusia affinis (fish, fresh water), LC50 = 13,000 mg/L/48 hours [Acetone]

Toxicity to daphnia and other aquatic invertebrates: Daphnia cucullata (Crustacea), EC50 = ca. 7,635 mg/L/48 hours [Acetone]

Toxicity to algae: Anabaena inaequalis (Algae), EC50 = 21,725 mg/L/14 days [Acetone]

Persistence and degradability: No data available Bioaccumulative potential: No data available Mobility in soil: No data available PBT and vPvB assessment: No data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Disposal considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

Section 14 Transport information

UN/NA number: UN1993 **Shipping name:** Flammable liquids, n.o.s., (Acetone, Ethyl alcohol)

Hazard class: 3 Packing group: || Reportable Quantity: 5,000 lbs (2270 kg) Marine pollutant: No

2020 ERG Guide # 128 **Exceptions:** Limited quantity equal to or less than 1 L

Section 15 Regulatory information

A chemical is considered to be listed if the CAS number for the anhydrous form is on the Inventory list

A continuous to both but to both but the of the number for the unity around form to on the involvery not.						
Component	TSCA	CERLCA (RQ)	RCRA code	DSL	NDSL	CA Prop 65
Acetone Ethanol	Listed Listed	5,000 lbs (2270 kg) Not listed	U002 D001	Listed Listed	Not listed Not listed	⚠ WARNING -Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Section 16 Other information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook

Revision Date: August 29, 2022 Supercedes: September 23, 2020 Form 06/2015

Section 1 Identification Page E1 of E2

INNOVATING SCIENCE

"Cutting edge science for the classroom"

by Aldon Corporation 221 Rochester Street Avon, NY 14414-9409 (585) 226-6177

CHEMTREC 24 Hour Emergency Phone Number (800) 424-9300

For laboratory and industrial use only. Not for drug, food or household use.

Product	COUMARIN 314 SOLUTION
Synonyms	Chromatography Dye Solution

Section 2 Hazards identification

Signal word: DANGER

Pictograms: GHS02 / GHS06 / GHS08

Target organs: Eyes, Central nervous system, Liver, Kidneys.







GHS Classification:

Flammable liquid (Category 2) Acute toxicity, oral (Category 3) Acute toxicity, dermal (Category 3) Acute toxicity, inhalation (Category 3) Eye irritation (Category 2B) STOT-SE (Category 2) STOT-SE (Category 3)

GHS Label information: Hazard statement:

H225: Highly flammable liquid and vapour.

H301: Toxic if swallowed

H311: Toxic in contact with skin.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H336: May cause drowsiness or dizziness.

H371: May cause damage to organs.

Precautionary statement:

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking

P233+P235: Keep container tightly closed. Keep cool. P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge

P260: Do not breathe mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated

clothing. Rinse skin with water/shower. P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for

breathing. P308+P311: IF exposed or concerned: Call a POISON CENTER or doctor.

P337+P313: If eye irritation persists: Get medical attention.

P361+P364: Take off immediately all contaminated clothing and wash it before reuse.

P370+P378: In case of fire: Use dry chemical, alcohol foam, carbon dioxide or water spray to extinguish.

P403+P405: Store in a well-ventilated place. Store locked up.

P501: Dispose of contents/container to a licensed chemical disposal agency in accordance with local/regional/national regulations.

Hazards not otherwise classified:

Health hazards not otherwise classified (HHNOC) - Not Known Physical hazards not otherwise classified (PHNOC) - Not Known

CAS # 64-17-5 5804-66-5	% 99.5% 0.5%	200-578-6 259-825-1	
5804-66-5	0.5%	259-825-1	
67-63-0		200-661-7	
67-56-1		200-659-6	
108-10-1		203-550-1	
	67-56-1	67-56-1	67-56-1 200-659-6

Section 4 First aid measures

INGESTION: TOXIC IF SWALLOWED. Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: TOXIC IF INHALED. CAUSES RESPIRATORY TRACT IRRITATION. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: CAUSES SERIOUS EYE IRRITATION. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN ABSORPTION: TOXIC IN CONTACT WITH SKIN. CAUSES SKIN IRRITATION. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

Section 5 Fire fighting measures

Suitable Extinguishing Media: Carbon dioxide, dry chemical, dry sand, alcohol foam.

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep

Specific Hazards: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Vapors formed from this product are heavier than air and may travel along the ground to a distant source of ignition and flash back instantly. Flame may not be visible in daylight.

Accidental release measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways

Containment and Cleanup: Remove all sources of ignition. Absorb with inert dry material, sweep or vacuum up and place in a suitable container for proper disposal. Wash spill area with soap and water.

Section 7 Handling and storage Page E2 of E2

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Avoid contact with eyes, skin and clothing. Do not inhale vapors, spray or mist. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, dry, well-ventilated area away from incompatible substances. Keep away from ignition sources.

Section 8	Exposure controls / personal protection						
Exposure Limits:	Chemical Name	ACGIH (TLV)	OSHA (PEL)	NIOSH (REL)			
Exposure Limits:	Ethanol	STEL: 1000 ppm / 1880 mg/m ³ (A3)	TWA: 1000 ppm / 1900 mg/m ³	TWA: 1000 ppm / 1900 mg/m ³			

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If misty conditions prevail, work in fume hood or wear a NIOSH/MSHA-approved respirator.

Section 9 Physical and chemical properties

Appearance: Fluorescent, yellow-green liquid. Odor: Mild characteristic odor. Odor threshold: Data not available.

pH: Data not available.

Melting / Freezing point: -114°C (-173°F)*
Boiling point: 74-80°C (165.2-176°F)*
Flash point: 14.4°C (58°F) TCC*

Evaporation rate (Butyl acetate = 1): Ca 2 Flammability (solid/gas): Data not available. Explosion limits: Lower / Upper: 3.3% / 19.0% Vapor pressure (mm Hg): Ca 50 @ 20°C

Vapor density (Air = 1): Ca 1.5

Relative density (Specific gravity): 0.7919-0.7955°C @ 60/60°F Solubility(ies): Soluble in water.

Viscosity: Data not available.

Molecular formula: Mixture

Molecular weight: Mixture

Partition coefficient: (n-octanol / water): Low Pow: -.32

Auto-ignition temperature: 363°C (685°F)

Decomposition temperature: Data not available

*[Ethanol]

Section 10 Stability and reactivity

Chemical stability: Stable Hazardous polymerization: Will not occur. Conditions to avoid: Excessive temperatures, heat, sparks, open flame and other sources of ignition.

Incompatible materials: Strong oxidizers, inorganic acids and halogens.

Hazardous decomposition products: Oxides of carbon.

Section 11 Toxicological information

Acute toxicity: Oral-rat LD50: 7060 mg/kg; Inhalation-rat LC50: 124.7 mg/l/4hours

Skin corrosion/irritation: Skin-rabbit - Slight irritant.
Serious eye damage/irritation: Eyes-rabbit - Severe irritant.
Respiratory or skin sensitization: Data not available

Germ cell mutagenicity: Data not available

Carcinogenity: Data not available

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

IARC classified: Group 3: Not classifiable as to its carcinogenicity to humans. [Isopropanol]

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

CA Prop 65: MWARNING!: This product can expose you to chemicals including Methanol and Methyl isobutyl ketone, which are known to the State of California to cause cancer and birth defects or other reproductive harm.

Reproductive toxicity: Data not available

STOT-single exposure: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT-repeated exposure: Data not available
Aspiration hazard: Data not available

Potential health effects:

Inhalation: Inhalation may cause dizziness, drowsiness, nausea, vomiting, inability to concentrate and irritation of the throat. Ingestion: Ingestion causes dizziness, drowsiness, decreased reaction, euphoria, nausea, vomiting, staggering gait and coma.

Skin: Contact with skin causes irritation defatting on prolonged contact.

Eyes: Contact with eyes may cause blindness.

Signs and symptoms of exposure: See Potential health effects above.

Additional information: RTECS #: KQ6300000

Section 12 Ecological information

Toxicity to fish: Oncorhynchus mykiss (fish, fresh water), LC50 = 11,200 mg/l/24 hours [Ethanol]

Toxicity to daphnia and other aquatic invertebrates: Daphnia magna (Crustacia), EC50 = 10,800 mg/l/24 hours [Ethanol, 99.8% pure]

Toxicity to algae: Chlorella pyrenoidosa (Algae), EC50 = 9,310 mg/l/growth rate [Ethanol, absolute]

Persistence and degradability: No data available

Mobility in soil: No data available

PBT and vPvB assessment: No data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Section 13 Disposal considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

Section 14 Transport information

UN/NA number: UN1170 **Shipping name:** Ethanol solution

Hazard class: 3 Packing group: II Reportable Quantity: 5,000 lbs (2270 kg) Marine pollutant: No

Exceptions: Limited quantity equal to or less than 1 L 2020 ERG Guide # 127

Section 15 Regulatory information

A chemical is considered to be listed if the CAS number for the anhydrous form is on the Inventory list.

Component	TSCA	CERLCA (RQ)	RCRA code	DSL	NDSL	CA Prop 65
Ethanol	Listed	Not listed	D001	Listed	Not listed	⚠ WARNING -Cancer and Reproductive Harm - www.P65Warnings.ca.gov.
Methanol	Listed	5,000 lbs.	U154	Listed	Not listed	
Isopropanol	Listed	Not listed	Not listed	Listed	Not listed	

Section 16 Other information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook.

Form 06/2015 Revision Date: September 8, 2022 Supercedes: September 24, 2020

Section 1 Identification Page E1 of E2

INNOVATING SCIENCE

"Cutting edge science for the classroom"

by Aldon Corporation 221 Rochester Street Avon, NY 14414-9409 (585) 226-6177 CHEMTREC 24 Hour Emergency Phone Number (800) 424-9300

For laboratory and industrial use only. Not for drug, food or household use.

Product METHYLENE BLUE DYE, 1% ALCOHOL SOLUTION

Synonyms Chromatography Dye Solution

Section 2 Hazards identification

Signal word: DANGER

Pictograms: GHS02 / GHS06 / GHS08

Target organs: Eyes, Central nervous system, Liver, Kidneys.







GHS Classification:

Flammable liquid (Category 2)
Acute toxicity, oral (Category 3)
Acute toxicity, dermal (Category 3)
Acute toxicity, inhalation (Category 3)
Eye irritation (Category 2B)
STOT-SE (Category 2)
STOT-SE (Category 3)

GHS Label information: Hazard statement:

H225: Highly flammable liquid and vapour.

H301: Toxic if swallowed.

H311: Toxic in contact with skin.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H336: May cause drowsiness or dizziness.

H371: May cause damage to organs.

Precautionary statement:

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking

P233+P235: Keep container tightly closed. Keep cool. P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P260: Do not breathe mist/vapours/spray. P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection. P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P311: IF exposed or concerned: Call a POISON CENTER or doctor.

P337+P313: If eye irritation persists: Get medical attention.

P361+P364: Take off immediately all contaminated clothing and wash it before reuse. P370+P378: In case of fire: Use dry chemical, alcohol foam, carbon dioxide or water spray to extinguish.

P403+P405: Store in a well-ventilated place. Store locked up.

P501: Dispose of contents/container to a licensed chemical disposal agency in accordance with local/regional/national regulations.

Hazards not otherwise classified:

Health hazards not otherwise classified (HHNOC) - Not Known Physical hazards not otherwise classified (PHNOC) - Not Known

Section 3 Composition / information on ingredients						
Chemical Name	CAS#	%	EINECS			
Ethyl alcohol, denatured* Methylene blue chloride	64-17-5 61-73-4	99% 1%	200-578-6 200-515-2			
*Denaturants: Isopropyl alcohol Water Methanol Methyl isobutyl ketone	67-63-0 7732-18-5 67-56-1 108-10-1		200-661-7 231-791-2 200-659-6 203-550-1			

Section 4 First aid measures

INGESTION: TOXIC IF SWALLOWED. Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: TOXIC IF INHALED. CAUSES RESPIRATORY TRACT IRRITATION. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: CAUSES SERIOUS EYE IRRITATION. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN ABSORPTION: TOXIC IN CONTACT WITH SKIN. CAUSES SKIN IRRITATION. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

Section 5 Fire fighting measures

Suitable Extinguishing Media: Carbon dioxide, dry chemical, dry sand, alcohol foam.

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep fire-exposed containers cool.

Specific Hazards: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Vapors formed from this product are heavier than air and may travel along the ground to a distant source of ignition and flash back instantly. Flame may not be visible in daylight.

Section 6 Accidental release measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways

Containment and Cleanup: Remove all sources of ignition. Absorb with inert dry material, sweep or vacuum up and place in a suitable container for proper disposal. Wash spill area with soap and water.

Page E2 of E2 Section 7 Handling and storage

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Avoid contact with eyes, skin and clothing. Do not inhale vapors, spray or mist. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, dry, well-ventilated area away from incompatible substances. Keep away from ignition sources.

Section 8	Exposure controls / personal protection						
Exposure Limits:	Chemical Name	ACGIH (TLV)	OSHA (PEL)	NIOSH (REL)			
Exposure Limits:	Ethanol	STEL: 1000 ppm / 1880 mg/m ³ (A3)	TWA: 1000 ppm / 1900 mg/m ³	TWA: 1000 ppm / 1900 mg/m ³			

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If misty conditions prevail, work in fume hood or wear a NIOSH/MSHAapproved respirator.

Section 9 Physical and chemical properties

Appearance: Clear, Blue liquid. Odor: Mild characteristic odor. Odor threshold: Data not available.

pH: Data not available Melting / Freezing point: -114°C (-173°F)* Boiling point: 74-80°C (165.2-176°F)*

Flash point: 5°C (41°F)*

Evaporation rate (Butyl acetate = 1): Ca 2* Flammability (solid/gas): Data not available. Explosion limits: Lower / Upper: 4.0%(V) / 20.0%(V)*

Vapor pressure (mm Hg): Ca 50 @ 20°C' Vapor density (Air = 1): Ca 1.5*

Relative density (Specific gravity): 0.7919-0.7955°C @ 60/60°F*

Solubility(ies): Soluble in water.

Partition coefficient: (n-octanol / water): Low Pow: -.32*

Auto-ignition temperature: 400°C (752°F)* Decomposition temperature: Data not available.

Viscosity: Data not available. Molecular formula: Mixture Molecular weight: Mixture

*[Ethanol]

Section 10 Stability and reactivity

Chemical stability: Stable Hazardous polymerization: Will not occur. Conditions to avoid: Excessive temperatures, heat, sparks, open flame and other sources of ignition.

Incompatible materials: Strong oxidizers, inorganic acids and halogens.

Hazardous decomposition products: Oxides of carbon.

Section 11 **Toxicological information**

Acute toxicity: Oral-rat LD50: 7060 mg/kg; Inhalation-rat LC50: 124.7 mg/l/4hours [Ethanol]

Skin corrosion/irritation: Skin-rabbit - Slight irritant. Serious eye damage/irritation: Eyes-rabbit - Severe irritant. Respiratory or skin sensitization: Data not available

Germ cell mutagenicity: Data not available

Carcinogenity: Data not available

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

IARC classified: Group 3: Not classifiable as to its carcinogenicity to humans. [Isopropanol]

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

CA Prop 65: 🛦 WARNING! : This product can expose you to chemicals including Methanol and Methyl isobutyl ketone, which are known to the State of California to cause cancer and birth defects or other reproductive harm.

Reproductive toxicity: Data not available

STOT-single exposure: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT-repeated exposure: Data not available Aspiration hazard: Data not available

Potential health effects:

Inhalation: Inhalation may cause dizziness, drowsiness, nausea, vomiting, inability to concentrate and irritation of the throat. Ingestion: Ingestion causes dizziness, drowsiness, decreased reaction, euphoria, nausea, vomiting, staggering gait and coma.

Skin: Contact with skin causes irritation defatting on prolonged contact.

Eyes: Contact with eyes may cause blindness.

Signs and symptoms of exposure: See Potential health effects above.

Additional information: RTECS #: KQ6300000 [Ethanol]

Ecological information

Toxicity to fish: Oncorhynchus mykiss (fish, fresh water), LC50 = 11,200 mg/l/24 hours [Ethanol]

Toxicity to daphnia and other aquatic invertebrates: Daphnia magna (Crustacia), EC50 = 10,800 mg/l/24 hours [Ethanol, 99.8% pure]

Toxicity to algae: Chlorella pyrenoidosa (Algae), EC50 = 9,310 mg/l/growth rate [Ethanol, absolute] Persistence and degradability: No data available Bioaccumulative potential: No data available Mobility in soil: No data available PBT and vPvB assessment: No data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Disposal considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

Section 14 Transport information

UN/NA number: UN1170 Shipping name: Ethanol

Reportable Quantity: 5,000 lbs (2270 kg) Hazard class: 3 Packing group: || Marine pollutant: No

2020 ERG Guide # 127 **Exceptions:** Limited quantity equal to or less than 1 L

Section 15 Regulatory information

A chemical is considered to be listed if the CAS number for the anhydrous form is on the Inventory list.

Component	TSCA	CERLCA (RQ)	RCRA code	DSL	NDSL	CA Prop 65
Ethanol	Listed	Not listed	D001	Listed	Not listed	▲ WARNING -Cancer and Reproductive Harm - www.P65Warnings.ca.gov.
Methanol	Listed	5,000 lbs.	U154	Listed	Not listed	
Isopropanol	Listed	Not listed	Not listed	Listed	Not listed	

Section 16 Other information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook

Revision Date: October 24, 2022 Supercedes: October 8, 2020 Form 06/2015

FLAMMABLE STORAGE CODE RED

Identification Section 1 Page E1 of E2

INNOVATING SCIENCE® by

"Cutting edge science for the classroom"

Aldon Corporation 221 Rochester Street Avon, NY 14414-9409 (585) 226-6177

CHEMTREC 24 Hour Emergency Phone Number (800) 424-9300

For laboratory and industrial use only. Not for drug, food or household use.

SUDAN IV, 0.5% IN ALCOHOL SOLUTION Product

Synonyms Chromatography Dye Solution - Red

Section 2 Hazards identification

Signal word: DANGER Pictograms: GHS02 / GHS07

Target organs: Central nervous system, Liver, Kidneys.





GHS Classification:

Flammable liquid (Category 2) Eye irritation (Category 2) STOT-SE (Category 3)

GHS Label information: Hazard statement(s):

H225: Highly flammable liquid and vapour. H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Precautionary statement(s):

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P261: Avoid breathing mist/vapours/spray. P264: Wash hands thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face

protection.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P312: Call a POISON CENTER or doctor if you feel unwell

P337+P313: If eye irritation persists: Get medical attention.

P370+P378: In case of fire: Use dry chemical, alcohol foam, carbon dioxide or

water spray to extinguish.

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

P501: Dispose of contents/container to a licensed chemical disposal agency in

accordance with local/regional/national regulations.

Hazards not otherwise classified:

Health hazards not otherwise classified (HHNOC) - Not Known Physical hazards not otherwise classified (PHNOC) - Not Known

Section 3 Composition / information on ingredients							
Chemical Name	CAS#	%	EINECS				
Isopropyl alcohol	67-63-0	99.5%	200-661-7				
Sudan IV, biological stain	85-83-6	0.5%	201-635-8				

Section 4 First aid measures

INGESTION: MAY BE HARMFUL IF SWALLOWED. Call physician or Poison Control Center immediately. Induce vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person.

INHALATION: MAY BE HARMFUL IF INHALED. CAUSES RESPIRATORY TRACT IRRITATION. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

EYE CONTACT: CAUSES EYE IRRITATION. Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention.

SKIN ABSORPTION: MAY BE HARMFUL IF ABSORBED THROUGH SKIN. MAY CAUSE SKIN IRRITATION. Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention.

Section 5 Fire fighting measures

Suitable Extinguishing Media: Carbon dioxide, dry chemical, dry sand, alcohol foam.

Protective Actions for Fire-fighters: In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective gear. Use water spray to keep

Specific Hazards: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Vapors formed from this product are heavier than air and may travel along the ground to a distant source of ignition and flash back instantly. Flame may not be visible in daylight.

Accidental release measures

Personal Precautions: Evacuate personnel to safe area. Use proper personal protective equipment as indicated in Section 8. Provide adequate ventilation.

Environmental Precautions: Avoid runoff into storm sewers and ditches which lead to waterways

Containment and Cleanup: Remove all sources of ignition. Absorb with inert dry material, sweep or vacuum up and place in a suitable container for proper disposal. Wash spill area with soap and water.

Page E2 of E2 Section 7 Handling and storage

Precautions for Safe Handling: Read label on container before using. Do not wear contact lenses when working with chemicals. Keep out of reach of children. Avoid contact with eyes, skin and clothing. Do not inhale vapors, spray or mist. Use with adequate ventilation. Avoid ingestion. Wash thoroughly after handling. Remove and wash clothing before reuse.

Conditions for Safe Storage: Store in a cool, well-ventilated area away from incompatible substances. Keep away from ignition sources.

Section 8	Exposure controls / personal protection						
Exposure Limits:	Chemical Name	ACGIH (TLV)	OSHA (PEL)	NIOSH (REL)			
Exposure Limits.	Isopropanol	TWA: 200 ppm / STEL: 400 ppm	TWA: 400 ppm / 980 mg/m ³	TWA: 400 ppm / STEL: 500 ppm			

Engineering controls: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower and fire extinguishing material. Personnel should wear safety glasses, goggles, or faceshield, lab coat or apron, appropriate protective gloves. Use adequate ventilation to keep airborne concentrations low.

Respiratory protection: None should be needed in normal laboratory handling at room temperatures. If misty conditions prevail, work in fume hood or wear a NIOSH/MSHAapproved respirator.

Physical and chemical properties Section 9

Appearance: Clear, red liquid.

Odor: Aromatic odor

Odor threshold: Data not available.

pH: Data not available

Melting / Freezing point: Approximately -50°C (-58°F)* Boiling point: Approximately 85-100°C (185-212°F)*

Flash point: 12°C (53°F) CC*

Evaporation rate (Butyl acetate = 1): >1 Flammability (solid/gas): Data not available. Explosion limits: Lower / Upper: 2% / 12%* Vapor pressure (mm Hg): 33 mm @20°C*

Vapor density (Air = 1): 2.1*

Relative density (Specific gravity): 0.8* Solubility(ies): Complete in water.

Partition coefficient: (n-octanol / water): Data not available

Auto-ignition temperature: 399°C (750°F) ASTM-E659-78* Decomposition temperature: Data not available.

Viscosity: Data not available. Molecular formu la: Mixture Molecular weight: Mixture

*Isopropyl alcohol

Section 10 Stability and reactivity

Chemical stability: Stable Hazardous polymerization: Will not occur. Conditions to avoid: Excessive temperatures, heat, sparks, open flame and other sources of ignition.

Incompatible materials: Strong oxidizing materials, caustics, aluminums, metals, nitroform, oleum, chlorinated compounds can react vigorously with this alcohol.

Hazardous decomposition products: Oxides of carbon.

Section 11 **Toxicological information**

Acute toxicity: Oral-rat LD50: 4396 mg/kg; Inhalation-rat LC50: 72.6 mg/L/4 hours; Dermal-rat LD50: 12,000 mg/kg [Isopropanol]

Skin corrosion/irritation: Skin-rabbit - Slight irritant. Serious eye damage/irritation: Eyes-rabbit - Irritating. Respiratory or skin sensitization: Not sensitizing Germ cell mutagenicity: Data not available

Carcinogenity: Data not available

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

IARC classified: Group 3: Not classifiable as to its carcinogenicity to humans [Isopropanol]

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Ca Prop 65: This product does not contain any chemicals known to the State of California to cause cancer or reproductive toxicity.

Reproductive toxicity: Data not available

STOT-single exposure: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects. [Isopropanol]

STOT-repeated exposure: Data not available

Aspiration hazard: Yes Potential health effects:

Inhalation: Inhalation of high vapor concentrations may cause central nervous system depression resulting in dizziness, drowsiness, nausea, vomiting, inability to concentrate and irritation of the throat. Continued inhalation may result in unconsciousness and death.

Ingestion: Aspiration hazard. Liquid can directly enter the lungs (aspirated) when swallowed or vomited. Serious lung damage and possible fatal chemical pneumonia can develop if this occurs.

Skin: Prolonged or repeated contact may cause irritation and drying, cracking and defatting of the skin which can lead to dermatitis. Eyes: Contact causes burning sensation, redness, swelling, and/or blurred vision.

Signs and symptoms of exposure: See Potential health effects above.

Additional information: RTECS #: NT8050000 [Isopropanol]

Section 12 **Ecological information**

Toxicity to fish: Pimephales promelas (Fish, fresh water) LC50: 9640 mg/L/96 hours [Isopropanol]

Toxicity to daphnia and other aquatic invertebrates: Artemia salina (Crustacea), EC50 = >10,000 mg/L/24 hours [Isopropanol]

Toxicity to algae: Scenedesmus quadricauda (Algae), LOEC50 = 1,800 mg/L/7 days [Isopropanol] Persistence and degradability: No data available Bioaccumulative potential: No data available Mobility in soil: No data available PBT and vPvB assessment: No data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Disposal considerations

These disposal guidelines are intended for the disposal of catalog-size quantities only. Federal regulations may apply to empty container. State and/or local regulations may be different. Dispose of in accordance with all local, state and federal regulations or contract with a licensed chemical disposal agency.

Section 14 Transport information

UN/NA number: UN1219 Shipping name: Isopropanol solution

Hazard class: 3 Packing group: || Reportable Quantity: No Marine pollutant: No

2020 ERG Guide # 129 **Exceptions:** Limited quantity equal to or less than 1 L

Section 15 Regulatory information

A chemical is considered to be listed if the CAS number for the anhydrous form is on the Inventory list.

Component	TSCA	CERLCA (RQ)	RCRA code	DSL	NDSL	CA Prop 65
Isopropyl alcohol	Listed	Not listed	Not listed	Listed		This product does not contain any chemicals known to the State of California to cause cancer or reproductive toxicity.

Section 16 Other information

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. NTP: National Toxicology Program, IARC: International Agency for Research on Cancer, OSHA: Occupational Safety and Health Administration, STOT: Specific Target Organ Toxicity, SE: Single Exposure, RE: Repeated Exposure, ERG: Emergency Response Guidebook

Revision Date: November 16, 2022 Supercedes: October 27, 2020 Form 06/2015